

Application Serial No. 09/463,541
Reply to Office Action of December 19, 2003

Patent
Docket: C.J-2114

Amendments To The Claims
(In The Revised Format)

The listing of claims presented below will replace all prior versions, and listings, of claims in the application.

Listing of claims:

1. (currently amended) A method of operating a communication network comprising a plurality of stations able to transmit data to and receive data from one another, the method comprising:

monitoring, at each station, the path quality between that station and each other station with which that station communicates;

recording, at each station, path quality data corresponding to the path quality associated with each said other station;

setting, at each station, a transmission power value based on the recorded path quality data associated with a selected other station when transmitting data to said selected other station, thereby to increase the probability of transmitting data to said selected other station at an optimum power level; and

transmitting path quality data corresponding to the path quality between a first and a second station when transmitting other data between the stations, so that path quality data recorded at the first station is communicated to the second station for use by the second station and vice versa, the method being characterized in that each station includes local background noise/interference data in at least some of its transmissions to other stations, for use by the other stations in adjusting their transmission power values when transmitting data to

Application Serial No. 09/463,541
Reply to Office Action of December 19, 2003

Patent
Docket: CU-2114

*cl
concl -*

said each station and in that it includes monitoring, from a first station transmitting data, the background noise/interference at a second station receiving a data transmission and adjusting the transmission power value at the station transmitting data to the receiving station, thereby to maintain the required signal to noise ratio at the receiving station.

*B
cont
Sub 17*

2. (original) A method according to claim 1 wherein the monitoring of path quality between stations includes monitoring at least one of the path loss, phase distortion, time delay, Doppler shift and multipath fading characteristics of a channel between the stations.

3. (previously presented) A method according to claim 2 wherein the path quality at a station receiving a data transmission is calculated by comparing the measured power of the received transmission with data in the transmission indicating the transmission power thereof.

4. (original) A method according to claim 3 wherein a station receiving such path quality data compares the received path quality data with respective stored path quality data and calculates a path quality correction value from a difference between the received and stored values, the path quality correction value being utilized to adjust the transmission power when transmitting data to the station which transmitted the path quality data.

5. (original) A method according to claim 4 wherein the path quality correction factor is calculated by deriving rate of change data from a plurality of path quality correction factor calculations.

6. (original) A method according to claim 5 wherein the rate of change data

Application Serial No. 09/463,541
Reply to Office Action of December 19, 2003

Patent
Docket: CU-2114

is utilized to adjust the transmission power predictively when transmitting data to a station whose path quality correction value is detected to be changing over time.

7. (currently amended) A method according to claim 6 wherein each station monitors the transmissions of other stations to obtain path quality data therefrom, so that a first station monitoring a transmission from a second station within range of the first station to a third station ~~out~~ out of range of the first station can obtain path quality data relating to the third station.

8-9. (cancelled)

10. (currently amended) A method according to ~~claim 9~~ claim 7 including adjusting the data rate of message data transmitted from a first station to a second station according to the transmission power value set at the first station and the required signal to noise ratio at the second station.

11. (previously presented) A method according to claim 10 including adjusting the length of message data packets transmitted from the first station to a second station according to the transmission power value set at the first station and the required signal to noise ratio at the second station.

12. (previously presented) A method according to claim 11 wherein each station monitors the transmission of other stations to obtain background noise/interference data therefrom, so that a first station monitoring a transmission from a second station within range of the first station to a third station out of range of the first station can obtain background noise/interference data relating to the third station.

Application Serial No. 09/463,541
Reply to Office Action of December 19, 2003

Patent
Docket: CU-2114

13. (previously presented) A method according to claim 12 including selecting, opportunistically, a station for transmission of data thereto according to the path quality and/or background noise/interference data associated therewith.

14 (currently amended) Communication apparatus operable as a station in a network comprising a plurality of stations which can transmit data to and receive data from one another, the communication apparatus comprising

transmitter means arranged to transmit data to selected stations;

receiver means arranged to receive data transmitted from other stations;

signal strength measuring means for measuring the power of received transmissions;

processor means for calculating and recording path quality data corresponding to the path quality associated with other stations; and

control means for adjusting the output power of the transmitter according to the path quality between the apparatus and a destination station,

wherein the processor means is arranged to include the path quality data in its transmissions to other stations for use by them, and to receive path quality data in transmissions from other stations for use in calculating updated path quality data, and further to monitor background noise/interference data in transmissions from other stations, so that a first station monitoring a transmission from a second station within range of the first station to a third station out of range of the first station can obtain background noise/interference data relating to the third station.

15. (original) Communication apparatus according to claim 14 wherein the

Application Serial No. 09/463,541
Reply to Office Action of December 19, 2003

Patent
Docket: CU-2114

C1
cancel - processor means is arranged to calculate the path quality by comparing data in received transmissions relating to their transmission power and/or a previously measured path quality with the measurements made by the signal strength measuring means.

Subcom
cont 16. (original) Communication apparatus according to claim 15 wherein the processor means is arranged to monitor at least one of the path loss, phase distortion, time delay, Doppler shift and multipath fading characteristics of a channel between the apparatus and other stations.

17. (previously presented) Communication apparatus according to claim 16 wherein the processor means is arranged to extract path quality data from received transmissions, to compare the path quality data with the measured power of received transmissions, and to calculate a path quality correction factor from the difference therebetween, the path quality correction factor being utilized by the control means to adjust the output power of the transmitter.

18. (original) Communication apparatus according to claim 17 wherein the processor means is adapted to derive rate of change data from a plurality of path quality correction factor calculations, thereby to compensate for variations in the path quality between stations.

19. (original) Communication apparatus according to claim 18 wherein the processor means is arranged to utilize the rate of change data to adjust the transmission power predictively when transmitting data to a station whose path quality correction value is detected to be changing over time.

cancel 20. (previously presented) Communication apparatus according to claim 19

Application Serial No. 09/463,541
Reply to Office Action of December 19, 2003

Patent
Docket: CU-2114

wherein the processor means is arranged to monitor path quality data in transmission from other stations, so that a first station monitoring a transmission from a second station within range of the first station to a third station out of the range of the first station can obtain path quality data relating to the third station.

21. (previously presented) Communication apparatus according to claim 20 wherein the processor means is arranged to store path quality data for each of a plurality of stations and to set an initial transmission power value when initiating communication with any one of said plurality of stations according to the respective stored path quality data.

22. (cancelled)

23. (currently amended) Communication apparatus according to ~~Claim 22~~ Claim 21 wherein the processor means is adapted to select, opportunistically, another station for transmission of data thereto according to the path quality and/or background noise/interference data associated therewith.